

# GAC<sup>®</sup> 2500-AGRI

## GRAIN ANALYSIS COMPUTER

Utilizes the same technology as elevator instruments to provide you with the highest level of confidence in your moisture reading.

DICKEY-john, the worldwide leader in grain moisture analyzers, offers the GAC<sup>®</sup> 2500-AGRI, an affordable moisture tester that provides elevator-like results.

The GAC 2500-AGRI uses the newest analysis technology (149 MHz) to provide repeatable results, just like the instruments at the elevator. One key benefit of 149 MHz technology is the reduction of grain calibrations required to deliver precise results. Additionally, the GAC 2500-AGRI has more accurate temperature sensing capabilities, allowing you to measure in extreme temperature conditions including frozen and hot grain. Operation is also simplified with an intuitive color touchscreen, providing accurate results regardless of user skill level.

### Features and Benefits:

- Utilizes 149 MHz technology to provide elevator-like results
- Easy-to-use, intuitive color touchscreen eliminates operator training
- Accurate temperature-sensing capabilities allow you to measure frozen and hot grain
- Memory storage for up to 3,000 measurements
- Multiple USB ports on the back of the unit for software upgrades, USB devices, printer and peripherals
- Additional USB ports located on the front of unit for easy calibration imports, as well as keyboard and mouse plug-ins for inputting set-up data

### Backed by the power of DICKEY-john:

When you buy a DICKEY-john GAC 2500-AGRI you get all the dependability and value you expect from DICKEY-john products. Like all DICKEY-john products, the GAC 2500-AGRI is designed, manufactured, and supported in the USA.



# GAC<sup>®</sup> 2500-AGRI

## GRAIN ANALYSIS COMPUTER



### Calibrations:

With the myriad of applications in the industry, DICKEY-john understands the need to modify moisture testers to suit the requirements of your region and operation. That is why the GAC 2500-AGRI is designed with a robust set of standard calibrations and supported with the option for expansion.

- Lowest legal temperatures, up to 20% moisture at -4 °F
- Highest moisture limit with unofficial hot grain calibrations
- Calibrations specifically developed for specialty crops such as peanuts, almonds, and popcorn
- Best-in-class support backed by DICKEY-john's onsite calibration laboratories
- Convenient, easy-to-download calibrations available on [www.dickey-john.com](http://www.dickey-john.com)
- Custom calibration development available for unique crop and region attributes

### Specifications

Operating temperature	36 to 113 °F (2 to 45 °C)
Power	110/220V, 50/60 Hz, 30/35 VA
Humidity	20 to 90% noncondensing
Grain temperature	-4 °F to +113 °F (-20 ° to +45 °C) depending on grain calibrations
Storage/transit temperature	-4 to +140 °F (-20 to +60 °C)
Moisture range	5 to 45% (grain dependent)
Approximate Weight	25 lbs. (11.43 kg)
Approximate dimensions	17" H x 19" W x 14" D (43.18cm H x 48.26cm W x 35.56 cm D)



Intuitive Color Touchscreen



Front USB Ports Accommodate Keyboard and Mouse Plug In



Easy-to-Read Results Screen